



A - ALUMINUM B=BRASS S=STEEL SS-STAINLESS

Ferrule Number	I.D.	Length	Hole	Metal Thick
A-330-S	0.330	0.490	0.250	0.025
A-350-S	0.350	0.500	0.220	0.025
A-375-L	0.375	0.718	0.265	0.025
A-375-SP1	0.375	0.718	0.312	0.025
A-400-L	0.400	0.718	0.265	0.025
A-410-SP1	0.410	0.500	0.281	0.025
A-425-L	0.425	0.718	0.265	0.025
A-425-SP1	0.425	0.718	0.300	0.025
A-425-SP2	0.425	0.718	0.328	0.025
A-450-L	0.450	0.718	0.328	0.025
A-450-S	0.450	0.500	0.265	0.025
A-450-SP1	0.450	0.718	0.270	0.025
A-475-L	0.475	0.718	0.328	0.025
A-475-S	0.475	0.500	0.328	0.025
A-480-L	0.480	0.750	0.300	0.025
A-500-L	0.500	0.718	0.328	0.025
A-500-S	0.500	0.500	0.328	0.025
A-500-SP5	0.500	0.718	0.400	0.025
A-525-L	0.525	0.718	0.406	0.025
A-525-S	0.525	0.500	0.406	0.025
A-525-SP1	0.525	0.500	0.425	0.025
A-525-SP11	0.525	0.562	0.328	0.025
A-525-SP9	0.525	0.718	0.328	0.025
A-550-L	0.550	0.718	0.406	0.025
A-550-S	0.550	0.550	0.406	0.025
A-550-SP5	0.550	0.718	0.328	0.025
A-575-L	0.575	0.968	0.406	0.025
A-575-S	0.575	0.500	0.406	0.025
A-600-L	0.600	0.968	0.453	0.025
A-600-S	0.600	0.550	0.453	0.025
A-600-SP1	0.600	0.468	0.453	0.025
A-625-L	0.625	0.968	0.453	0.025
A-625-S	0.625	0.550	0.453	0.025
A-650-L	0.650	0.968	0.453	0.025
A-650-S	0.650	0.500	0.453	0.025
A-650-SP5	0.650	0.718	0.484	0.025
A-675-L	0.675	0.968	0.500	0.025
A-675-S	0.675	0.500	0.500	0.025
A-700-L	0.700	0.968	0.500	0.025
A-700-S	0.700	0.575	0.500	0.025
A-725-L	0.725	0.968	0.500	0.025
A-725-S	0.725	0.550	0.500	0.025
A-750-L	0.750	0.968	0.500	0.025
A-750-S	0.750	0.550	0.500	0.025
A-775-L	0.775	0.968	0.593	0.025
A-775-S	0.775	0.500	0.593	0.025
A-800-L	0.800	0.968	0.593	0.025
A-800-S	0.800	0.500	0.593	0.025
A-825-L	0.825	0.968	0.687	0.025
A-825-S	0.825	0.550	0.687	0.025
A-825-SP3	0.825	0.968	0.500	0.025
A-850-L	0.850	0.968	0.687	0.025
A-850-S	0.850	0.550	0.687	0.025
A-870-L	0.870	1.000	0.670	0.025
A-875-L	0.875	0.968	0.750	0.025
A-875-S	0.875	0.500	0.750	0.025
A-900-L	0.900	0.968	0.750	0.025
A-900-S	0.900	0.550	0.750	0.025
A-925-L	0.925	0.968	0.750	0.025
A-925-S	0.925	0.550	0.750	0.025
A-950-L	0.950	0.968	0.750	0.025
A-950-S	0.950	0.500	0.750	0.025
A-950-SP3	0.950	0.968	0.625	0.025
A-950-SP6	0.950	0.968	0.625	0.040
A-975-L	0.975	0.968	0.875	0.040
A-1000-L	1.000	0.968	0.875	0.040

Ferrule Number	I.D.	Length	Hole	Metal Thick
A-1025-L	1.025	0.968	0.875	0.040
A-1050-L	1.050	0.968	0.875	0.040
A-1075-L	1.075	0.968	0.875	0.040
A-1100-L	1.100	0.968	0.875	0.040
A-1125-L	1.125	0.968	0.875	0.040
A-1125-SP1	1.125	0.875	0.875	0.025
A-1150-L	1.150	0.968	0.875	0.040
A-1175-L	1.175	0.968	0.875	0.040
A-1175-SP1	1.175	0.875	0.875	0.025
A-1200-L	1.200	0.968	1.000	0.040
A-1225-L	1.225	0.968	1.000	0.040
A-1250-L	1.250	0.968	1.000	0.040
A-1325-L	1.325	0.968	1.047	0.040
A-1350-L	1.350	1.250	1.125	0.040
A-1380-S	1.380	0.843	1.047	0.025
A-1425-SP1	1.425	0.875	1.062	0.025
A-1437-SP1	1.437	0.968	1.047	0.040
A-1468-S	1.468	0.812	1.125	0.025
A-1500-L	1.500	1.000	1.125	0.040
B-275-S	0.275	0.500	0.217	0.020
B-312-L	0.312	0.500	0.225	0.020
B-330-S	0.330	0.490	0.250	0.020
B-330-SP1	0.330	0.500	0.260	0.020
B-330-SP3	0.330	0.375	0.250	0.020
B-340-L	0.340	0.750	0.219	0.025
B-358-S	0.358	0.500	0.265	0.020
B-375-L	0.375	0.718	0.265	0.025
B-375-S	0.375	0.437	0.265	0.025
B-380-S	0.380	0.500	0.265	0.020
B-400-L	0.400	0.718	0.265	0.025
B-400-S	0.400	0.437	0.265	0.025
B-400-SP2	0.400	0.470	0.270	0.020
B-400-SP3	0.400	0.718	0.313	0.025
B-410-S	0.410	0.500	0.265	0.020
B-410-SP1	0.410	0.500	0.281	0.020
B-410-SP2	0.410	0.465	0.265	0.020
B-410-SP3	0.410	0.715	0.281	0.025
B-425-L	0.425	0.718	0.265	0.025
B-425-S	0.425	0.450	0.265	0.025
B-425-SP1	0.425	0.718	0.300	0.025
B-425-SP2	0.425	0.718	0.328	0.025
B-438-L	0.438	0.718	0.325	0.020
B-438-SP1	0.438	0.718	0.270	0.020
B-450	0.450	0.720	0.270	0.020
B-450-L	0.450	0.718	0.328	0.025
B-450-S	0.450	0.500	0.265	0.025
B-450-SP1	0.450	0.718	0.270	0.025
B-450-SP1-S	0.450	0.562	0.343	0.020
B-450-SP5	0.450	0.710	0.250	0.025
B-450-SP6	0.450	1.000	0.330	0.025
B-450-SP9	0.450	0.718	0.328	0.020
B-450-SP10	0.450	1.000	0.245	0.025
B-466-L	0.466	0.675	0.328	0.020
B-475-L	0.475	0.718	0.328	0.025
B-475-LB	0.475	0.718	0.265	0.025
B-475-S	0.475	0.500	0.328	0.025
B-475-SP1	0.475	1.000	0.328	0.025
B-475-SP2	0.475	0.718	0.328	0.020
B-475-SP3	0.475	1.000	0.265	0.025
B-478-L	0.478	0.687	0.328	0.025
B-500-L	0.500	0.718	0.328	0.025
B-500-S	0.500	0.500	0.328	0.025
B-500-SP1	0.500	1.000	0.343	0.025
B-500-SP2	0.500	0.500	0.343	0.020
B-500-SP3	0.500	1.000	0.328	0.025
B-500-SP4	0.500	0.718	0.265	0.025

Ferrule Number	I.D.	Length	Hole	Metal Thick
B-500-SP6	0.500	0.718	0.410	0.025
B-525-L	0.525	0.718	0.406	0.025
B-525-S	0.525	0.500	0.406	0.025
B-525-SP10	0.525	0.500	0.406	0.020
B-525-SP3	0.525	1.000	0.375	0.025
B-525-SP4	0.525	1.000	0.437	0.025
B-525-SP5	0.525	0.560	0.360	0.020
B-525-SP6	0.525	0.470	0.360	0.020
B-525-SP9	0.525	0.718	0.328	0.025
B-531-L	0.531	1.000	0.375	0.025
B-550-L	0.550	0.718	0.406	0.025
B-550-S	0.550	0.550	0.406	0.025
B-550-SP1	0.550	0.718	0.340	0.025
B-550-SP1-S	0.550	0.484	0.375	0.020
B-550-SP3	0.550	0.750	0.350	0.025
B-550-SP5	0.550	0.718	0.328	0.025
B-550-SP6	0.550	0.968	0.391	0.025
B-550-SP8	0.550	0.750	0.422	0.025
B-560-L	0.560	1.000	0.375	0.025
B-560-SP1	0.560	1.000	0.437	0.025
B-560-SP2	0.560	0.750	0.375	0.020
B-575-L	0.575	0.968	0.406	0.025
B-575-S	0.575	0.500	0.406	0.025
B-575-SP1	0.575	0.484	0.468	0.020
B-593-L	0.593	1.000	0.437	0.025
B-600-L	0.600	0.968	0.453	0.025
B-600-S	0.600	0.550	0.453	0.025
B-600-SP1	0.600	0.968	0.350	0.025
B-600-SP2	0.600	0.500	0.500	0.020
B-600-SP3	0.600	0.500	0.406	0.025
B-600-SP4	0.600	0.968	0.391	0.025
B-600-SP5	0.600	0.718	0.391	0.020
B-600-SP7	0.600	0.375	0.391	0.020
B-625-L	0.625	0.968	0.453	0.025
B-625-S	0.625	0.550	0.453	0.025
B-625-SP3	0.625	0.500	0.500	0.020
B-625-SP4	0.625	1.000	0.437	0.025
B-625-SP5	0.625	0.968	0.265	0.025
B-625-SP6	0.625	1.000	0.265	0.025
B-625-SP7	0.625	1.000	0.375	0.025
B-625-SP8	0.625	1.000	0.500	0.025
B-640-L	0.640	1.000	0.437	0.025
B-650-L	0.650	0.968	0.453	0.025
B-650-S	0.650	0.500	0.453	0.025
B-650-SP1	0.650	0.750	0.455	0.020
B-650-SP2	0.650	0.500	0.406	0.025
B-650-SP3	0.650	0.500	0.500	0.020
B-656-L	0.656	1.000	0.437	0.025
B-656-SP1	0.656	1.000	0.332	0.025
B-675-L	0.675	0.968	0.500	0.025
B-675-S	0.675	0.500	0.500	0.025
B-675-SP1	0.675	0.625	0.500	0.025
B-675-SP2	0.675	0.515	0.500	0.020
B-675-SP3	0.675	0.968	0.453	0.025
B-675-SP5	0.675	0.968	0.590	0.025
B-690-L	0.690	1.000	0.500	0.025
B-700-L	0.700	0.968	0.500	0.025
B-700-S	0.700	0.575	0.500	0.025
B-700-SP1	0.700	0.625	0.453	0.025
B-700-SP2	0.700	0.968	0.406	0.025
B-700-SP4	0.700	0.530	0.500	0.020
B-700-SP6	0.700	0.968	0.562	0.025
B-718-SP1	0.718	1.000	0.500	0.025
B-718-SP2	0.718	1.000	0.625	0.025
B-725-L	0.725	0.968	0.500	0.025
B-725-S	0.725	0.550	0.500	0.025



A - ALUMINUM B=BRASS S=STEEL SS=STAINLESS

Ferrule Number	I.D.	Length	Hole	Metal Thick
B-725-SP3	0.725	0.530	0.500	0.020
B-750-L	0.750	0.968	0.500	0.025
B-750-S	0.750	0.550	0.500	0.025
B-750-SP1	0.750	0.875	0.438	0.025
B-750-SP3	0.750	1.000	0.625	0.025
B-750-SP4	0.750	1.000	0.500	0.025
B-750-SP5	0.750	0.531	0.500	0.020
B-775-L	0.775	0.968	0.593	0.025
B-775-S	0.775	0.500	0.593	0.025
B-775-SP2	0.775	0.531	0.500	0.020
B-781-SP1	0.781	1.000	0.500	0.025
B-781-SP2	0.781	1.000	0.625	0.025
B-800-L	0.800	0.968	0.593	0.025
B-800-S	0.800	0.500	0.593	0.025
B-800-SP2	0.800	0.546	0.562	0.020
B-812-L	0.812	1.000	0.625	0.025
B-812-SP1	0.812	1.000	0.420	0.025
B-825-L	0.825	0.968	0.687	0.025
B-825-S	0.825	0.550	0.687	0.025
B-825-SP1	0.825	0.968	0.506	0.025
B-825-SP2	0.825	0.546	0.562	0.020
B-825-SP4	0.825	0.968	0.593	0.025
B-850-L	0.850	0.968	0.687	0.025
B-850-S	0.850	0.550	0.687	0.025
B-850-SP1	0.850	0.968	0.593	0.025
B-870-L	0.870	1.000	0.670	0.025
B-875-L	0.875	0.968	0.750	0.025
B-875-S	0.875	0.500	0.750	0.025
B-875-SP1	0.875	0.843	0.687	0.025
B-875-SP2	0.875	0.968	0.500	0.025
B-875-SP3	0.875	0.530	0.750	0.020
B-900-L	0.900	0.968	0.750	0.025
B-900-S	0.900	0.550	0.750	0.025
B-900-SP2	0.900	0.875	0.687	0.025
B-900-SP3	0.900	0.968	0.593	0.025
B-900-SP4	0.900	0.562	0.750	0.020
B-925-L	0.925	0.968	0.750	0.025
B-925-S	0.925	0.550	0.750	0.025
B-925-SP1	0.925	0.843	0.687	0.025
B-925-SP2	0.925	0.968	0.593	0.025
B-925-SP3	0.925	1.000	0.540	0.025
B-937-L	0.937	0.875	0.750	0.025
B-937-SP1	0.937	0.843	0.687	0.025
B-950-L	0.950	0.968	0.750	0.025
B-950-S	0.950	0.500	0.750	0.025
B-950-SP2	0.950	0.750	0.750	0.025
B-975-L	0.975	0.968	0.875	0.040
B-975-SP2	0.975	0.843	0.687	0.025
B-975-SP4	0.975	0.968	0.625	0.040
B-1000-L	1.000	0.968	0.875	0.040
B-1000-SP2	1.000	0.843	0.687	0.025
B-1000-SP4	1.000	0.593	0.750	0.020
B-1025-L	1.025	0.968	0.875	0.040
B-1025-SP1	1.025	0.843	0.687	0.025
B-1050-L	1.050	0.968	0.875	0.040
B-1050-SP1	1.050	0.843	0.687	0.025
B-1075-L	1.075	0.968	0.875	0.040
B-1100-L	1.100	0.968	0.875	0.040
B-1100-SP1	1.100	0.687	0.875	0.025
B-1100-SP2	1.100	0.843	0.812	0.025
B-1125-L	1.125	0.968	0.875	0.040
B-1125-SP1	1.125	0.875	0.875	0.025
B-1125-SP2	1.125	0.625	0.875	0.025
B-1150-L	1.150	0.968	0.875	0.040
B-1150-SP1	1.150	0.625	0.875	0.020
B-1150-SP2	1.150	0.843	0.875	0.025

Ferrule Number	I.D.	Length	Hole	Metal Thick
B-1175-L	1.175	0.968	0.875	0.040
B-1175-SP1	1.175	0.875	0.875	0.025
B-1175-SP2	1.175	0.625	0.875	0.020
B-1200-L	1.200	0.968	1.000	0.040
B-1200-S	1.200	0.750	1.000	0.025
B-1200-SP1	1.200	0.968	1.000	0.025
B-1200-SP2	1.200	0.843	0.875	0.025
B-1225-L	1.225	0.968	1.000	0.040
B-1225-S	1.225	0.781	1.094	0.025
B-1225-SP1	1.225	0.968	0.875	0.025
B-1250-L	1.250	0.968	1.000	0.040
B-1250-SP1	1.250	0.875	1.000	0.025
B-1275-SP1	1.275	0.968	0.875	0.025
B-1325-L	1.325	0.968	1.047	0.040
B-1350-L	1.350	1.250	1.125	0.040
B-1375-S	1.375	0.875	1.125	0.025
B-1380-S	1.380	0.843	1.047	0.025
B-1425-SP1	1.425	0.875	1.062	0.025
B-1437-SP1	1.437	0.968	1.047	0.040
B-1468-L	1.468	1.250	1.125	0.040
B-1468-S	1.468	0.812	1.125	0.025
B-1468-SP1	1.468	1.215	1.125	0.040
B-1500-L	1.500	1.000	1.125	0.040
B-1500-S	1.500	0.875	1.125	0.025
B-1525-S	1.525	0.812	1.125	0.025
B-1550-L	1.550	0.968	1.125	0.040
B-1550-S	1.550	0.812	1.125	0.025
S-550-SP6	0.550	0.968	0.391	0.025
S-560-L	0.560	1.000	0.375	0.025
S-575-L	0.575	0.968	0.406	0.025
S-605-SP6	0.605	1.400	0.380	0.033
S-690-L	0.690	1.000	0.500	0.025
S-710-SP6	0.710	1.400	0.485	0.033
S-765-L-PHLS	0.765	1.400	0.380	0.033
S-790-SP6	0.790	1.400	0.615	0.033
S-850-SP1	0.850	0.968	0.593	0.025
S-925-L-PHLS	0.925	1.400	0.485	0.033
S-960-SP6	0.960	1.400	0.660	0.033
S-1032-L-PHLS	1.032	1.400	0.615	0.033
S-1150-L-PHLS	1.150	1.400	0.710	0.033
S-1175-L	1.175	0.968	0.875	0.040
SS-438-L	0.438	0.718	0.325	0.016
SS-478-L	0.478	0.687	0.328	0.020
SS-530-L	0.531	1.000	0.438	0.020
SS-560-L	0.560	1.000	0.437	0.020
SS-564-L	0.564	0.750	0.375	0.020
SS-593-L	0.593	1.000	0.437	0.020
SS-600-L	0.600	0.968	0.453	0.020
SS-625-SP4	0.625	1.000	0.437	0.020
SS-656-L	0.656	1.000	0.437	0.020
SS-690-L	0.690	1.000	0.500	0.020
SS-718-SP1	0.718	1.000	0.625	0.020
SS-750-L	0.750	0.968	0.500	0.020
SS-750-SP3	0.750	1.000	0.625	0.020
SS-781-SP2	0.781	1.000	0.625	0.020
SS-812-L	0.812	1.000	0.625	0.020
SS-925-L	0.925	0.968	0.750	0.020
SS-1075-L	1.075	0.968	0.875	0.025
SS-1175-L	1.175	0.968	0.875	0.025
SS-1175-SP1	1.175	0.844	0.875	0.020
SS-1250-L	1.250	0.968	1.000	0.025

Ferrule Number	I.D.	Length	Hole	Metal Thick
NON-STOCK STEEL - MIN REQUIRES				
IF NOT AVAILABLE, MINIMUM ORDER 5,000 PIECES WITH A SETUP CHARGE OF \$1,250 (PER PART)				
S-330-S	0.330	0.490	0.250	0.020
S-330-SP1	0.330	0.500	0.260	0.020
S-358-S	0.358	0.500	0.265	0.020
S-380-S	0.380	0.500	0.265	0.020
S-400-SP2	0.400	0.470	0.270	0.020
S-410-S	0.410	0.500	0.265	0.020
S-425-S	0.425	0.450	0.265	0.025
S-425-SP1	0.425	0.718	0.300	0.025
S-425-SP2	0.425	0.718	0.328	0.025
S-450-L	0.450	0.718	0.328	0.025
S-450-SP1-S	0.450	0.562	0.343	0.020
S-450-SP6	0.450	1.000	0.330	0.025
S-450-SP9	0.450	0.718	0.328	0.020
S-475-L	0.475	0.718	0.328	0.025
S-475-LB	0.475	0.718	0.265	0.025
S-475-S	0.475	0.500	0.328	0.025
S-475-SP3	0.475	1.000	0.265	0.025
S-500-L	0.500	0.718	0.328	0.025
S-500-SP4	0.500	0.718	0.265	0.025
S-525-L	0.525	0.718	0.406	0.025
S-525-SP3	0.525	1.000	0.375	0.025
S-525-SP9	0.525	0.718	0.328	0.025
S-550-L	0.550	0.718	0.406	0.025
S-550-S	0.550	0.550	0.406	0.025
S-550-SP1-S	0.550	0.484	0.375	0.020
S-550-SP5	0.550	0.718	0.328	0.025
S-560-SP2	0.560	0.750	0.375	0.020
S-575-S	0.575	0.500	0.406	0.025
S-593-L	0.593	1.000	0.437	0.025
S-600-SP2	0.600	0.500	0.500	0.020
S-600-SP3	0.600	0.500	0.406	0.025
S-600-SP5	0.600	0.718	0.391	0.020
S-625-L	0.625	0.968	0.453	0.025
S-625-SP4	0.625	1.000	0.437	0.025
S-625-SP7	0.625	1.000	0.375	0.025
S-650-L	0.650	0.968	0.453	0.025
S-650-S	0.650	0.500	0.453	0.025
S-650-SP1	0.650	0.750	0.455	0.020
S-656-L	0.656	1.000	0.437	0.025
S-675-L	0.675	0.968	0.500	0.025
S-700-L	0.700	0.968	0.500	0.025
S-700-SP4	0.700	0.530	0.500	0.020
S-718-SP1	0.718	1.000	0.500	0.025
S-725-L	0.725	0.968	0.500	0.025
S-800-L	0.800	0.968	0.593	0.025
S-812-L	0.812	1.000	0.625	0.025
S-850-L	0.850	0.968	0.687	0.025
S-900-L	0.900	0.968	0.750	0.025
S-925-L	0.925	0.968	0.750	0.025
S-925-SP20	0.925	1.000	0.540	0.025
S-1075-L	1.075	0.968	0.875	0.040
S-1125-SP1	1.125	0.875	0.875	0.025
S-1150-SP2	1.150	0.843	0.875	0.025
S-1250-L	1.250	0.968	1.000	0.040
S-1380-S	1.380	0.843	1.047	0.025
S-1468-L	1.468	1.250	1.125	0.033